



QLE406xC Family

Single or Dual-Port 1Gbps iSCSI to PCI Express Adapter

High Performance

- Networking and storage functionality for iSCSI, network attached storage (NAS), clustering, multimedia, distributed network applications, and web-serving
- Jumbo frames, 802.3x Flow Control, 802.1p Priority Service, and 802.1Q Virtual LAN (VLAN) Ethernet Networking
- Auto-negotiated 100/1000Mbps line rate data transfer

Superior Scalability


- Low-profile PCI Express® form factor
- Universal iSCSI SAN boot for true remote storage boot implementations

Enhanced Reliability

- Storage reliability with iSCSI digests, error correction codes (ECC) memory, and overlapping data path parity
- JTAG boundary scan, full scan, and memory built-in self-test (BIST)
- Highly integrated, low-power design

Simplified Manageability

- Microsoft® Windows® management interface (MS WMI) compliant for standards-based management



SANs with Ethernet and IP: iSCSI. IT managers now have a choice when considering SAN management options. The QLE4060C and QLE4062C (collectively referred to as the QLE406xC) iSCSI adapters provide connectivity to SANs over Ethernet and TCP/IP network infrastructures for PCI Express bus-based servers. Using a widely deployed and familiar networking technology, iSCSI can lower the total cost of ownership to better manage and support storage networking.

Networking and Storage Performance. By offloading the iSCSI and TCP/IP protocol to the adapter, the QLE406xC eliminates the processing, interrupts, and bus accesses required to support protocols in host software. The QLE406xC virtually eliminates the host CPU system processing required for iSCSI and TCP/IP, delivering the equivalent performance of direct attached storage (DAS) and Fibre Channel SANs.

IPv6 Support. QLogic is the first to offer IPv6 support in an iSCSI TCP/IP offload engine (TOE) adapter. IPv6 is the next generation of IP addressing, which quadruples the number of network address bits from 32 bits (in IPv4) to 128 bits (in IPv6). As networks migrate to the updated IP protocol, IT managers can be assured that the QLE406xC will interoperate in emerging network environments.

Familiar Storage Functionality. The QLE406xC utilizes the existing storage interface of the operating system. Using a familiar storage interface allows the QLE406xC to support proven logical unit number (LUN) and target-level fail-over functionality, storage SAN boot, and existing SAN management and application software.

Comprehensive Operating System (OS) Support. QLogic offers the broadest range of support for all major operating systems to ensure OS and hardware server compatibility. Drivers are fully tested with industry-recognized certifications from all the major operating systems, including Windows, Linux®, Solaris®, Citrix®, Oracle®, and VMware®.

Guaranteed Interoperability. Storage partner certifications, combined with agency and regulatory testing, ensure that all products meet world compliance hardware and software specifications. All adapters are tested extensively with third-party hardware and multiple software applications, to ensure best-in-class SAN interoperability and compatibility. You can be confident purchasing QLogic adapters to meet your storage networking needs.

QLE406xC Family Single or Dual-Port 1Gbps iSCSI to PCI Express Adapter

Host Bus Interface Specifications

Bus interface

- 2.5 GHz PCI Express x4

Hardware platforms

- IA32 (x86)
- EM64T
- AMD® Opteron™ 64
- Sun™ SPARC®

Compliance

- PCI Express Base Specification rev. 1.0a, PCI Express Card Electromechanical Specification rev. 1.0, PCI Bus Power Management Interface Specification revision. 1.1

iSCSI, TCP/IP, and Ethernet Specifications

Data rate

- 100/1000Mbps

Throughput

- 1Gbps full-duplex line rate

Topology

- Any Ethernet network

iSCSI

- RFC 3347
 - iSCSI Requirements and Design Considerations
 - CHAP
 - Internet simple name service (iSNS)

TCP/IP

- Complete state-based TCP/IP off-load, RFC791
- Internet Protocol Specification (IPv4), RFC793
- Transmission Control Protocol (TCP) Specification, RFC1122
- Requirements for Internet Hosts—Communication Layers, RFC1323
- TCP Extensions for High Performance, RFC2581
- TCP Congestion Control, RFC2460
- IPv6

Ethernet

- 1,500 bytes or 9,000 bytes (jumbo)

Physical Specifications

Ports

- QLE4060C: One
- QLE4062C: Two

Connections

- RJ45 for copper connector
- Form factor
- Low-profile: 16.93 cm × 5.15 cm (6.7 in. × 2.5 in.)

Bracket size

- Standard: 1.84 cm × 12.08 cm (.73 in. × 4.76 in.)
- Low-profile: 1.84 cm × 8.01 cm (.73 in. × 3.15 in.)

Environment and Equipment Specifications

Temperature

- Operating: 0°C/32°F to 55°C/131°F
- Storage: -20°C/-4°F to 70°C/158°F

Airflow

- 100 FPM (0.5m/S)

Humidity

- Relative (non-condensing): 10% to 90%
- Storage: 5% to 95%

Power dissipation

- QLE4060C: 9.6W (maximum)
- QLE4062C: 10.7W (maximum)

RoHS compliant

- RoHS 6

Cable distances

- 100 meters, category 5e/6 UTP

Tools and Utilities

Management tools

- SANsurfer® iSCSI Host Bus Adapter Manager

Device utilities

- CLI
- Utilities for flashing BIOS and firmware

Boot support

- BIOS
- FCode
- APIs
- MS WMI

Operating systems

- Windows 2000
- Windows Server® 2003, 2008, 2008 R2
- Windows Vista™ (Business and Enterprise)
- Windows XP Pro, XP Pro x64
- Novell® SLES 9.x, 10.x, 11.x
- Citrix XenServer 4.x, 5.x
- Oracle® OEL 4, 5
- Red Hat® RHEL 4.x, 5.x
- Solaris® 9, 10
- VMware® ESX/ESXi 3.5.x, 4.x

Ordering Information

QLE4060C-BK

- Ships in a bulk box in quantities of 20 or 50 with standard size brackets

QLE4060C-CK

- Ships in an individually packed box with a standard size bracket, a spare low-profile bracket, a SANsurfer for SANblade® iSCSI Adapters CD, and a Quick Start Guide

QLE4062C-BK

- Ships in a bulk box in quantities of 20 or 50 with standard size brackets

QLE4062C-CK

- Ships in an individually packed box with a standard size bracket, a spare low-profile bracket, a SANsurfer for SANblade iSCSI Adapters CD, and a Quick Start Guide



QLOGIC

The Ultimate in Performance



Corporate Headquarters

Europe Headquarters



QLogic Corporation 26650 Aliso Viejo Parkway Aliso Viejo, CA 92656 949.389.6000

www.qlogic.com

QLogic (UK) LTD. Quatro House Lyon Way, Frimley Camberley Surrey, GU16 7ER UK +44 (0) 1276 804 670

© 2006–2010 QLogic Corporation. Specifications are subject to change without notice. All rights reserved worldwide. QLogic, the QLogic logo, SANblade, and SANsurfer are registered trademarks of QLogic Corporation. Windows, Windows Server, and Windows Vista are registered trademarks of Microsoft Corporation. Linux Red Hat and Linux SuSE are registered trademarks of Red Hat, Inc. Linux is a registered trademark of Linus Torvalds. Sun is a trademark of Sun Microsystems, Inc. Solaris is a registered trademark of Sun Microsystems, Inc. Citrix is a registered trademark of Citrix Systems, Inc. AMD is a registered trademark of Advanced Micro Devices, Inc. Oracle is a registered trademark of Oracle Corporation. VMware is a registered trademark of VMware, Inc. PCI Express is a registered trademark of PCI-SIG Corporation. Novell is a registered trademark of Novell, Inc. SPARC is a registered trademark of SPARC International, Inc. in the USA and other countries. All other brand and product names are trademarks or registered trademarks of their respective owners. Information supplied by QLogic Corporation is believed to be accurate and reliable. QLogic Corporation assumes no responsibility for any errors in this brochure. QLogic Corporation reserves the right, without notice, to make changes in product design or specifications.